

Feb 26, 10 9:51

matmult.c

Page 1/2

```

// -----
// matrix multiplication
//
// 0. choose appropriate compiler version e.g.
//
//    source /S120S/apps/INTEL/cc/10.1.017/bin/iccvars.sh
//
// 1. compile with openmp support enabled and MKL library included
//
//    icc -O3 -openmp -openmp-report2
//        -I /opt/intel/mkl/current/include -L /opt/intel/mkl/current/lib/64
//        -lmkl matmult.c -o matmult
//
// 2. set number of threads and prohibit dynamic adjustment of number
//
//    export set OMP_DYNAMIC=FALSE
//    export set OMP_NUM_THREADS=<number of threads>
//
// 3. prepare runtime monitoring in other window showing all threads
//
//    top -u <username> -H
//
// 4. execute with timing switched on
//
//    time ./matmult
// -----

```

```

#include <stdio.h>
#include <stdlib.h>
#include <omp.h>

#include "mkl_gmp.h"

#define N 300

mpz_t A[N][N], B[N][N], C[N][N];

int main(int argc, char *argv[])
{
    int i, j, k;
    mpz_t s, p;

    // initialize A and B
    for (i=0; i<N; i++)
    {
        for (j=0; j<N; j++)
        {
            mpz_init(A[i][j]);
            mpz_init(B[i][j]);
            mpz_init(C[i][j]);

            mpz_set_si(A[i][j], rand()); // A[i][j] = rand()
            mpz_set_si(B[i][j], rand()); // B[i][j] = rand()
        }
    }

    // print part of A and B
    mpz_out_str(stdout, 10, A[0][0]); printf("\n");
    mpz_out_str(stdout, 10, B[0][0]); printf("\n");

```

```
// -----  
// parallel matrix multiplication:  
// iterations of outer loop are distributed among multiple threads  
// 1. make sure that local variables of outer loop are thread-private  
// 2. choose schedule e.g. static distribution of loop iterations  
// -----  
#pragma omp parallel for private(j,k,s,p) schedule(static)  
for (i=0; i<N; i++)  
{  
    // s and p must be initialized within each thread  
    mpz_init(s);  
    mpz_init(p);  
    for (j=0; j<N; j++)  
    {  
        mpz_set_si(s, 0); // s = 0  
        for (k=0; k<N; k++)  
        {  
            mpz_mul(p, A[i][k], B[k][j]); // p = A[i][k]*B[k][j]  
            mpz_add(s, s, p); // s = s+p  
        }  
        mpz_set(C[i][j], s); // C[i][j] = s  
    }  
}  
  
// print part of C  
mpz_out_str(stdout, 10, C[0][0]); printf("\n");  
}
```