


Object-Oriented Programming in C++ (Course “Computer Systems”)

Wolfgang Schreiner
Wolfgang.Schreiner@risc.jku.at

Research Institute for Symbolic Computation (RISC)
Johannes Kepler University, Linz, Austria
<http://www.risc.jku.at>






1. Overview

2. Development

3. Graphical Output

4. Text Input and Output

Overview



A continuation of the course “Programming” in the last semester.

- **Last semester:** procedural (“imperative”) programming in C++.
 - Focus on organization of control flow.
 - Passive entities (“data”) processed by active entities (“functions”).
 - Programs organized as sets of functions.
- **This semester:** object-oriented programming in C++.
 - Focus on organization of data.
 - “Classes” combine data and functions to “objects”.
 - Programs organized as sets of classes.

Modern approach to “programming in the large”.

Example




```
struct Date {
    int day;
    int month;
}

static void print(Date d)
{
    cout << d.day << "."
         << d.month << ".";
}

Date d;
d.day = 24;
d.month = 12;
print(d);
```

```
class Date {
private:
    int day;
    int month;
public:
    Date(int d, int m) {
        day = d;
        month = m;
    }
    void print() {
        cout << day << "."
             << month << ".";
    }
}

Date d = Date(24, 12);
d.print();
```




- **Classes:** combining data and functions.
 - Classes versus records (“structs”).
 - Construction, destruction, assignments.
 - Static members versus non-static members.
- **Inheritance:** building class hierarchies.
 - Classes and subclasses.
 - Virtual functions and overriding.
 - Abstract classes, interfaces, frameworks.
- **Templates:** type-generic (“polymorphic”) programming.
 - Function templates.
 - Class templates.
- **The C++ Standard Library:** reusing existing functionality.
 - Basic features (I/O, numerics, etc).
 - Containers, iterators, and algorithms.

Organization




- **Lecture:** concepts and examples.
 - Slides, blackboard, online demonstrations.
- **Assignments:** moderate programming exercises.
 - 6 assignments are given.
 - Results to be submitted within 2 weeks.
 - Tutors: Katharina Riegler and Gernot Hauzenberger.
 - See the course site for the date of the meeting offered every week.
- **Grades:** based on final exam and assignments.
 - Final exam (50%): concepts and small programming tasks.
 - Assignments (50%): best 5 results are evaluated.
 - Both exam and assignments have to be positive.
- **Literature:** no lecture notes, get a C++ textbook!
 - C++ is complex and involves many details.
 - Lecture notes could not provide a reasonable substitute.

Literature



- Arnold Willemer, *C++. Der Einstieg*, Wiley-VCH Verlag, 2013.
- 10 chapters, 500 pages.
- Chapters 1–4: previous semester.
- Chapters 5, 7.1, 8, 10: this semester.
- EUR 24,99 (Amazon).

Compact C++ introduction in German.




Literature



- Jürgen Wolf, *C++: Das umfassende Handbuch, aktuell zum Standard C++11*, Galileo Computing, 3. Auflage, 2014.
- 10 chapters, 1200 pages.
- Chapters 1–3: previous semester.
- Chapters 4-5: this semester.
- EUR 39,90 (Amazon).

Comprehensive C++ introduction in German.




Literature



- Stanley B. Lippman, Barbara E. Moo, Josee Lajoie *C++ Primer*, Addison-Wesley, 5th edition, 2012.
- 19 chapters + appendix, 900 pages.
- Chapters 1–6: previous semester.
- Chapters 7–16: this semester.
- EUR 40,95 (Amazon).

Comprehensive C++ introduction in English.




Literature



- Bjarne Stroustrup, *The C++ Programming Language*, 4th edition, Addison-Wesley, 2013.
- 44 chapters, 1300 pages.
- Chapters 1–15: previous semester.
- Chapters 16–33: this semester.
- EUR 51,95 (Amazon).

Not an introduction, but the full reference.




Literature



- Ray Lischner, *C++ in a Nutshell*, O'Reilly, 2003.
- 12 chapters language (300 pages) + 1 chapter library (400 pages).
- Chapters 1–5: previous semester.
- Chapters 6–10: this semester.
- EUR 26,22 (Amazon).

Not an introduction, but a compact reference.





Free Resources

Plenty of free resources in the web.

- C++ language tutorial.
 - <http://www.cplusplus.com/doc/tutorial>
 - 140 pages (PDF), short overview of main language features.
- C++ library reference.
 - <http://www.cplusplus.com/reference>.
 - A hypertext reference for the C++ standard library.
- Bruce Eckel, Thinking in C++, 2nd Edition.
 - <http://www.mindview.net/Books/TICPP/ThinkingInCPP2e.html>
 - Free electronic book, Volumes 1+2 (PDF, 800 pages each).

See the course site.

Moodle Course



Central point for electronic communication.

- Register as a participant in the Moodle course.
 - All forum messages will be sent as emails to registered participants.
- Submit assignments via Moodle.
 - No email submissions are accepted.
- Post questions in the “Questions and Answers” forum.
 - Answered by Wolfgang Schreiner or by one of the tutors.

<http://www.risc.jku.at/people/schreine/courses/ss2015/compsys>




1. Overview

2. Development

3. Graphical Output

4. Text Input and Output

C++ Development



Free integrated development environments (IDEs) for C++.

- Eclipse IDE for C/C++ Developers

<http://www.eclipse.org/downloads>

- GNU/Linux and MacOS X: The GNU C++ Compiler.

- Debian: `apt-get install g++`

- Windows: MinGW and MSYS.

<http://www.mingw.org>

<http://max.berger.name/howto/cdt>

- Microsoft Visual Studio Express 2013 for Windows Desktop

<http://www.microsoft.com/visualstudio/deu/downloads>

A decent IDE makes program development much more productive.

Eclipse IDE for C/C++ Developers



```
/*
 * HelloWorld.cpp
 * Created on: 03.09.2008
 * Author: schreine
 */

#include <iostream>


using namespace std;

int main()
{
    char message[] = "Hello, World!";
    cout << message;
    cout.flush();
}
```

C-Build [HelloWorld]
Building target: HelloWorld
Invoking: GCC C++ Linker
g++ -o "HelloWorld" ./Date.o ./HelloWorld.o
Finished building target: HelloWorld

Good support for development and for correcting compilation errors.

Eclipse Debug View



Learn to use a debugger for correcting runtime errors!



1. Overview

2. Development

3. Graphical Output

4. Text Input and Output

Graphical Output




Not in the C++ standard but system-dependent.

- We provide a small portable library for drawing pictures.
 - Based on the CImg library <http://cimg.sourceforge.net>
 - Works for GNU/Linux, Microsoft Windows, MacOS X.
- Library consists of three source files:
 - `Drawing.h`
 - `Drawing.cpp`
 - `CImg.h`
- Download files from course site and use for your programs.
 - `Drawing.h` must be included in sources.
 - `Drawing.cpp` (includes `CImg.h`) has to be compiled and linked to executable program.
- Usage is demonstrated in file `Main.cpp`.

See the course site for more information.

Example (file Main.cpp)





```
#include "Drawing.h"
using namespace compsys;


const unsigned int BLACK = 0x000000;
const unsigned int WHITE = 0xFFFFFFFF;
...

int main() {
    beginDrawing(400, 300, "A Graphical Program");
    drawLine(20, 20, 220, 120);
    drawRectangle(20, 20, 200, 200, BLUE);
    fillRectangle(60, 60, 120, 120, BLUE);
    drawEllipse(21, 21, 198, 198, GREEN);
    fillellipse (getWidth()/3, getHeight()*2/3, 500, 300, ORANGE);
    int xs[] = { 300, 350, 250 }; int ys[] = { 20, 100, 100 };
    drawPolygon(3, xs, ys, GREEN);
    int xs0[] = { 300, 350, 250 }; int ys0[] = { 100, 20, 20 };
    fillPolygon(3, xs0, ys0, WHITE, BLACK);
    drawText(10, 280, "My Picture");
    for (int i=0; i<getWidth(); i++) drawPoint(i, 10);
    endDrawing();
}
```

Example



Interface (file Drawing.h)



```
void beginDrawing(int width, int height, const char *title,
                  unsigned int color = 0xFFFFFFFF, bool flush = true);
void endDrawing();
void flush();
int getWidth();
int getHeight();
void drawPoint(int x, int y, unsigned int color = 0);
void drawLine(int x0, int y0, int x1, int y1, unsigned int color = 0);
void drawRectangle(int x, int y, int w, int h, unsigned int color = 0);
void fillRectangle(int x, int y, int w, int h,
                  unsigned int fcolor = 0, unsigned int ocolor = NO_COLOR);
void drawEllipse(int x, int y, int w, int h, unsigned int color = 0);
void fillellipse(int x, int y, int w, int h,
                unsigned int fcolor = 0, unsigned int ocolor = NO_COLOR);
void drawPolygon(int n, int* xs, int *ys, unsigned int color = 0);
void fillPolygon(int n, int* xs, int *ys,
                unsigned int fcolor = 0, unsigned int ocolor = NO_COLOR);
void drawText(int x, int y, const char *text,
              int size = 14, unsigned int color = 0);
```

See "Drawing.h" for the detailed specification of the interface.




1. Overview

2. Development

3. Graphical Output

4. Text Input and Output

C Standard Input/Output



Also in C++, the standard I/O functions of C can be used.

```
#include <cstdio>
using namespace std;

int main() {
    char day[20]; int hour; int min;
    printf("Day:    "); scanf("%19s", day);
    printf("Hour:   "); scanf("%d", &hour);
    printf("Minute: "); scanf("%d", &min);
    printf("%s, %.2d:%.2d\n", day, hour, min);
}
```

```
Day:    Monday
Hour:   6
Minute: 5
Monday, 06:05
```

Low-level and unsafe, C++ provides better alternatives.

C++ I/O Streams



C++ I/O is based on the concept of “streams”.

- **Stream**: an abstraction of an input/output device.
 - A sequence of characters (bytes) flowing from/to a source/sink.
- Stream sources/sinks may be **physical devices**.
 - Console, keyboard, disk file, ...
 - Characters written/read are physically input/output.
 - Class `fstream` (file streams).
- Stream sources/sinks may be **abstract devices**.
 - Strings, buffers, ...
 - Characters written/read are transferred to/from data object.
 - Class `stringstream` (string streams).

By this abstraction, the same program can operate without significant modification on a multitude of different devices.



I/O Operators

The shift operators are overloaded for all kinds of streams.

- **Writing: `operator<<`**
 - `out << val`: write value `val` to output stream `out`.
- **Reading: `operator>>`**
 - `in >> var`: read value from input stream `in` into variable `var`.
- **Typical: chaining of multiple operations on a stream.**
 - Write multiple values to an output stream:
`out << val1 << val2 << ...;`
 - Read multiple values from an input stream:
`in >> var1 >> var2 >> ...;`

The operators can be also overloaded for user-defined datatypes.

Reading a Sequence of Values




A common pattern for reading a sequence of values.

```
while (true)
{
    int input;
    cin >> input;
    if (!cin) break;
    ... // process input
}
```

- The conversion of a stream to a boolean indicates the success of the last operation on that stream.
 - If `!cin` yields “false”, the last operation on `cin` has failed (e.g. because of an unsuccessful attempt to read from the stream).

Check the status of input stream after every read operation!

I/O Manipulators



Manipulators can be inserted into a stream to influence its behavior.

```
out << val1 << endl << val2; // insert new line
in  >> var1 >> ws  >> var2; // eat white space
```

- **<iostream>**: input/output manipulators.
 - endl: insert new line and flush.
 - ends: insert null character and flush.
 - flush: flush stream buffer.
 - ws: eat white space.
- **<ios>**: formatting flags manipulators.
 - dec/hex/oct: use decimal/hexadecimal/octal number base.
 - skipws/noskipws: (do not) skip white space.
 - ...
- **<iomanip>**: parameterized manipulators.
 - setprecision(*n*): set output precision to *n* digits.
 - setw(*n*): set field width of output to *n* characters.
 - ...

I/O Manipulators



cplusplus.com: “C++ Reference”.


Independent flags (switch on):

<code>boolalpha</code>	Alphanumerical bool values (manipulator function)
<code>showbase</code>	Show numerical base prefixes (manipulator function)
<code>showpoint</code>	Show decimal point (manipulator function)
<code>showpos</code>	Show positive signs (manipulator function)
<code>skipws</code>	Skip whitespaces (manipulator function)
<code>unitbuf</code>	Flush buffer after insertions (manipulator function)
<code>uppercase</code>	Generate upper-case letters (manipulator function)

Independent flags (switch off):

<code>noboolalpha</code>	No alphanumerical bool values (manipulator function)
<code>noshowbase</code>	Do not show numerical base prefixes (manipulator function)
<code>noshowpoint</code>	Do not show decimal point (manipulator function)
<code>noshowpos</code>	Do not show positive signs (manipulator function)
<code>noskipws</code>	Do not skip whitespaces (manipulator function)
<code>nounitbuf</code>	Do not force flushes after insertions (manipulator function)
<code>nouppercase</code>	Do not generate upper case letters (manipulator function)

Example



cplusplus.com: “C++ Reference”.

```
#include <iostream>
using namespace std;

int main () {
    char a[10], b[10];

    cin >> noskipws;
    cin >> a >> ws >> b;
    cout << a << "," << b << endl;

    return 0;
}
```


Input:

```
one
    two
```

Output:

```
one,two
```

I/O Manipulators



Numerical base format flags ("basefield" flags):

dec Use decimal base (manipulator function)
hex Use hexadecimal base (manipulator function)
oct Use octal base (manipulator function)

Floating-point format flags ("floatfield" flags):

fixed Use fixed-point notation (manipulator function)
scientific Use scientific notation (manipulator function)

Adjustment format flags ("adjustfield" flags):

internal Adjust field by inserting characters at an internal position (m.f.)
left Adjust output to the left (manipulator function)
right Adjust output to the right (manipulator function)

Input manipulators

ws Extract whitespaces (manipulator function)

Output manipulators

endl Insert newline and flush (manipulator function)
ends Insert null character (manipulator function)
flush Flush stream buffer (manipulator function)



Example

cplusplus.com: “C++ Reference”.

```
#include <iostream>
using namespace std;

int main () {
    int n;
    n=70;
    cout << dec << n << endl;
    cout << hex << n << endl;
    cout << oct << n << endl;
    return 0;
}
```

```
70
46
106
```


I/O Manipulators




cplusplus.com: “C++ Reference”.

Parameterized manipulators

These functions take parameters when used as manipulators. They require the explicit inclusion of the header file `<iomanip>`.

<code>setiosflags</code>	Set format flags (manipulator function)
<code>resetiosflags</code>	Reset format flags (manipulator function)
<code>setbase</code>	Set basefield flag (manipulator function)
<code>setfill</code>	Set fill character (manipulator function)
<code>setprecision</code>	Set decimal precision (manipulator function)
<code>setw</code>	Set field width (manipulator function)

Example



cplusplus.com: "C++ Reference".

```
#include <iostream>
#include <iomanip>
using namespace std;

int main () {
    double f = 3.14159;
    cout << setprecision (5) << f << endl; // up to 5 digits (both sides of ".")
    cout << setprecision (9) << f << endl; // up to 9 digits (both sides of ".")
    cout << fixed;
    cout << setprecision (5) << f << endl; // exactly 5 digits to the right of "."
    cout << setprecision (9) << f << endl; // exactly 9 digits to the right of "."
    return 0;
}
```

```
3.1416
3.14159
3.14159
3.141590000
```



Example

plusplus.com: “C++ Reference”.

```
#include <iostream>
using namespace std;

int main () {
    int n;
    n=-77;
    cout << setw(6);
    cout << internal << n << endl;
    cout << left << n << endl;
    cout << right << n << endl;
    return 0;
}

-   77
-77
  -77
```

String Streams



cplusplus.com: “C++ Reference”

```
stringstream  
Input/output string stream class
```


```
class (header <sstream>)
```

stringstream provides an interface to manipulate strings as if they were input/output streams.

The objects of this class maintain internally a pointer to a stringbuf object that can be obtained/modified by calling member rdbuf. This stringstream-derived object controls a sequence of characters (string) that can be obtained/modified by calling member str.

We can use I/O operations to construct strings and parse them.

Example



cplusplus.com: “C++ Reference” (modified).

```
#include <iostream>
#include <sstream>
using namespace std;


int main () {
    int val;
    stringstream ss;

    ss << "120 42 377 6 5 2000";

    for (int n=0; n<6; n++)
    {
        ss >> val;
        cout << val*2 << endl;
    }

    return 0;
}
```

File Streams



plusplus.com: “C++ Reference”.

`fstream`

Input/output file stream class

`fstream` provides an interface to read and write data from files as input/output streams.

The objects of this class maintain internally a pointer to a `filebuf` object that can be obtained by calling member `rdbuf`.


The file to be associated with the stream can be specified either as a parameter in the constructor or by calling member `open`.

After all necessary operations on a file have been performed, it can be closed (or disassociated) by calling member `close`. Once closed, the same file stream object may be used to open another file.

The member function `is_open` can be used to determine whether the stream object is currently associated with a file.

File streams represent the contents of files (not the file system data).

Examples




```
#include <fstream>
#include <iostream>
using namespace std;

// read from file in.txt, let constructor open file
int main () {
    fstream in ("in.txt", fstream::in);
    if (!in) return;
    // input operations (in >> var)
    in.close();
    return 0;
}

// append to file out.txt, call open() for opening file
int main () {
    fstream out;
    out.open("out.txt", fstream::out | fstream::app);
    if (!out) return;
    // output operations (out << value)
    out.close();
    return 0;
}
```

Constructing a File Stream



plusplus.com: “C++ Reference”.

```
fstream::fstream    constructor member
```

```
fstream ( );  
explicit fstream ( const char * filename,  
                  ios_base::openmode mode = ios_base::in | ios_base::out );
```

Construct object and optionally open file

Constructs an object of the `fstream` class. This implies the initialization of the associated `filebuf` object and the call to the constructor of its base class with the `filebuf` object as parameter.

Additionally, when the second constructor version is used, the stream is associated with a physical file as if a call to the member function `open` with the same parameters was made.

If the constructor is not successful in opening the file, the object is still created although no file is associated to the stream buffer and the stream's `failbit` is set (which can be checked with inherited member `fail`).

Opening a File Stream



cplusplus.com: “C++ Reference”.

`fstream::open` public member function

```
void open ( const char * filename,  
            ios_base::openmode mode = ios_base::in | ios_base::out );
```

Open file


Opens a file whose name is `s`, associating its content with the stream object to perform input/output operations on it. The operations allowed and some operating details depend on parameter `mode`.

The function effectively calls `rdbuf()->open(filename,mode)`.

If the object already has a file associated (`open`), the function fails.

On failure, the `failbit` flag is set (which can be checked with member `fail`), and depending on the value set with `exceptions` an exception may be thrown.

File Modes



`ios_base::openmode` public member type

Bitmask type to represent stream opening mode flags. A value of this type can be any valid combination of the following member constants:

flag value	opening mode
<code>app</code>	(append) Set the stream's position indicator to the end of the stream before each output operation.
<code>ate</code>	(at end) Set the stream's position indicator to the end of the stream on opening.
<code>binary</code>	(binary) Consider stream as binary rather than text.
<code>in</code>	(input) Allow input operations on the stream.
<code>out</code>	(output) Allow output operations on the stream.
<code>trunc</code>	(truncate) Any current content is discarded, assuming a length of zero on opening.

These constants are defined in the `ios_base` class as public members. Therefore, they can be referred to either directly by their name as `ios_base` members (like `ios_base::in`) or by using any of their inherited classes or instantiated objects, like for example `ios::ate` or `cout.out`.

Closing a File Stream



cplusplus.com: “C++ Reference”.

```
fstream::close public member function
```

```
void close ( );
```

Close file

Closes the file currently associated with the object, disassociating it from the stream. Any pending output sequence is written to the physical file.


The function effectively calls `rdbuf()->close()`.

The function fails if no file is currently open (associated) with this object.

On failure, the `failbit` internal state flag is set (which can be checked with member `fail`), and depending on the value set with `exception` an exception may be thrown.

Before a file stream is closed, it is not guaranteed that data are on disk.

Flushing a Stream



cplusplus.com: “C++ Reference”.

```
ostream::flush public member function
```

```
ostream& flush ( );
```

Flush output stream buffer

Synchronizes the buffer associated with the stream to its controlled output sequence. This effectively means that all unwritten characters in the buffer are written to its controlled output sequence as soon as possible ("flushed").

The function only has meaning for buffered streams, in which case it effectively calls the `pubsync` member of the `streambuf` object (`rdbuf()->pubsync()`) associated to the stream.

A manipulator exists with the same name and behavior (see `flush` manipulator).

Typically applied in long running programs to make sure that output generated so far is on disk (not all data are lost when computer fails).

Example



cplusplus.com: “C++ Reference”.

```
#include <fstream>
using namespace std;


int main () {
    fstream outfile ("test.txt", ios::out);

    for (int n=0; n<100; n++) {
        outfile << n << " "; // alternative: outfile << n << " " << flush;
        outfile.flush();
    }

    outfile.close();

    return 0;
}
```

Input/Output File Streams



plusplus.com: “C++ Reference”.

```
ifstream class
```

Input file stream

ifstream provides an interface to read data from files as input streams.

```
ifstream( );
```

```
explicit ifstream (const char* filename, ios_base::openmode mode = ios_base::in);
```

```
void open(const char* filename, ios_base::openmode mode = ios_base::in);
```

```
ofstream class
```

Output file stream

ofstream provides an interface to write data to files as output streams.


```
ofstream( );
```

```
explicit ofstream(const char* filename, ios_base::openmode mode = ios_base::out);
```

```
void open(const char* filename, ios_base::openmode mode = ios_base::out);
```

Specialized to support only the corresponding read/write operations.

Copying a File of Integers




```
#include <iostream>
#include <fstream>
using namespace std;

int intFileCopy(char* inName, char* outName) throw(string);

int main(int argc, char* argv[]) {
    if (argc != 3) {
        cout << "Usage: intCopy <infile> <outfile>" << endl;
        return -1;
    }
    try {
        int n = intFileCopy(argv[1], argv[2]);
        cout << n << " values copied" << endl;
    }
    catch(string& message) {
        cerr << "Error: " << message << endl;
    }
    return 0;
}
```

Copying a File of Integers (Contd)



```
int intFileCopy(char* inName, char* outName) throw(string) {
    ifstream in(inName);
    if (!in) throw string("could not open input file");

    ofstream out(outName);
    if (!out) { in.close(); throw string("could not open output file"); }

    int i = 0;
    while (true) {
        int input;
        in >> input;
        if (!in) break;
        out << input << endl;
        i = i+1;
    }

    in.close();
    out.close();

    return i;
}
```